



AWVMS VARIABLE MESSAGE BOARD

11 Boeing Place, Mount Maunganui 3116 Ph: 07 575 0505

2/11 March Place, Belfast, Christchurch 8051 Ph: 03 323 7507

Email: admin@trafficsigns.co.nz www.trafficsigns.co.nz PO Box 4366, Mount Maunganui South 3149

ADVANCE WARNING VARIABLE MESSAGE BOARD NZTA CoPTTM Compliant



- ◆ Maximum running time is 45 hours at full pixels before recharging is required
- ◆ Normal battery operating specifications are 3 x 12 volt Deep Gel Cell batteries
- ◆ Unit is controlled by on-board tablet with 87 pre-programmed graphic/text sequences and five favourite tabs for simple efficient use
- ◆ All panels have auto and manual light sensors for changing light conditions
- ◆ Unit stands 3.65m once fully erected
- ◆ Vehicle mount, trailer mount or unit mount options available
- ◆ 3 legged support system for stand alone option
- ◆ Vehicle can be wired with specialised plug (as supplied) to assist with the charging the batteries
- ◆ Lifting Frame/Gear 12 month warranty T&C apply

QUALITY TRAFFIC SIGNS & ACCESSORIES AT COMPETITIVE PRICES

CONTACT US NOW FOR A QUOTATION

Visit our website www.trafficsigns.co.nz





VARIABLE MESSAGE TRAFFIC SIGN NZTA CoPTTM Compliant

11 Boeing Place, Mount Maunganui 3116 Ph: 07 575 0505
2/11 March Place, Belfast, Christchurch 8051 Ph: 03 323 7507

Email: admin@trafficsigns.co.nz www.trafficsigns.co.nz PO Box 4366, Mount Maunganui South 3149

MAIN FEATURES OF THE AWVMS:

- ◆ Custom built software for NZ market with pre-programmed favourites and simple to use tablet control
- ◆ Manufactured in Europe and tested to meet EN Standards
- ◆ AWVMS Board 24 Mth Warranty - T&C apply
- ◆ 5 Colour



DIMENSIONS:

- ◆ AWS panel 1380mm x 1380mm
- ◆ AWS actual display 1190mm x 1190mm
- ◆ VMS panel 1620mm x 1380mm
- ◆ VMS actual display 1450mm x 1190mm
- ◆ 80 x 80 Pixels - 15mm pixel pitch
- ◆ AWS 6400 - VMS 7680 LED's as per NZTA Photo Metrix requirements

ENVIRONMENTAL DATA:

- ◆ Temperature T1, T2, T3, (EN12966-1)
Range: from - 40°C to +60 °C
- ◆ Humidity: Up to 100%
- ◆ Mechanical P3 (EN 12966-1) IP56
Protection: (IEC / EN 60529)

OPTICAL CHARACTERISTICS:

- ◆ Pixel distance: 15mm
- ◆ Classifications: C2, L3, B6, R2
(EN 12966-1:2005 + A1:2009)
- ◆ Luminance Regulation: Light sensors
(default) day time or selection

XENON LIGHTS

- ◆ 340mm diameter amber light
- ◆ Compliant to European Std EN12352:2006
- ◆ Loop timing can be changed to allow for flashing sequence

QUALITY TRAFFIC SIGNS & ACCESSORIES AT COMPETITIVE PRICES

CONTACT US NOW FOR A QUOTATION

Visit our website www.trafficsigns.co.nz



Quality
ISO 9001



Health &
Safety
ISO 45001



Environment
ISO 14001

