



# ROAD TRAFFIC CONES

11 Boeing Place, Mount Maunganui 3116 Ph: 07 575 0505

2/11 March Place, Belfast, Christchurch 8051 Ph: 03 323 7507

Email: admin@trafficsigns.co.nz www.trafficsigns.co.nz PO Box 4366, Mount Maunganui South 3149

## TOP QUALITY - 12 MONTH GUARANTEE

Against splitting or breakage of cone (excluding reflective)

TTMC - NZTA Compliant - One piece construction - UV stabilized

### SLIM PROFILE

Available in 2 sizes:

<b>CODE:</b>	<b>WEIGHT:</b>
SP-4	4.3KG
SP-6	6.2KG

All cones now feature our **PRISMATIC**

**REFLECTIVE BANDS**  
**STRONGER - BRIGHTER**

### WIDE PROFILE

Available in 1 size:

<b>CODE:</b>	<b>WEIGHT:</b>
WP-4	4.3KG



**ROAD MARKER**  
450mm



**CONE COLLARS**  
Can be sold separately



**CONE DIVIDER**  
Extends to 2 metres



Option available for screen printing in your company name





# PRISMATIC CONE COLLARS

11 Boeing Place, Mount Maunganui 3116 Ph: 07 575 0505  
 2/11 March Place, Belfast, Christchurch 8051 Ph: 03 323 7507

Email: [admin@trafficsigns.co.nz](mailto:admin@trafficsigns.co.nz) [www.trafficsigns.co.nz](http://www.trafficsigns.co.nz) PO Box 4366, Mount Maunganui South 3149

## TRAFFIC SIGNS PRISMATIC CONE COLLARS

- ◆ Traffic Signs use Prismatic Wide Observation Angle reflective which is resilient to tearing, ripping or breaking, whereas the alternative glass bead technology is far more brittle
- ◆ Traffic Signs collars have superior day time colour - “white” not “grey”
- ◆ Traffic Signs collars have superior retroreflective performance at night with over twice the candela intensity rating of glass bead class 1 technology

Traffic Signs NZ Ltd's  
Cone & Collar



Alternative  
Cones & Collars  
on the market

(Example of 12 mths use )



### Test Method:

AS/NZS 1906.1:2007 Retroreflective materials and devices for road control purposes Part 1: Retroreflective sheeting

### Test Results:

Test Item (s)		Test Results (s)	AS/NZS Class 1 Values
Coefficient of Luminous Intensity ( $R_A$ ) ( $cd \cdot 1x^{-1} \cdot m^{-2}$ )	Observation Angle $\alpha$	Entrance Angle $\beta_1$ ( $\beta_2 = 0^\circ$ )	-
	0.2°	4°	841
	0.33°	4°	635
	0.5°	4°	778
	1.0°	4°	46
			Minimum 250
			Minimum 170
			Minimum 95
			Minimum 10

